



## G80 Welded D Ring

ITEM NO.	WLL/T	Dimensions/ mm								Weight Kg
		A	B	C	D	E	F	H	W	
YD085-01	1.12T	41	35	38	13	36	33	81	67	0.4
YD085-02	2T	42	41.5	40	14	38	35.5	91	70	0.47
YD085-03	3.15T	45	41.5	43	17.5	43	39	98	80	0.69
YD085-05	5.3T	54	48	60	22	50	49	119	98	1.46
YD085-08	8T	70	60	69	27	66	58	145	124	2.5
YD085-10	10T	84	81	75	28	76	62	171	140	3.2
YD085-15	15T	95	86	87	34	88	69	189	163	5.79
YD085-20	20T	147	146.5	125	46	124	88	280.5	239	15.5

★ safety factor: 4:1

## Safety Information

Load style										
Number of pieces	1	2	1	2	2	2	3-4	3-4	3-4	
Inclination angle	0°	0°	90°	90°	0-45°	45-60°	Asymmetry	0-45°	45-60°	Asymmetry

ITEM NO.	SIZE	WLL / T									
		1	2	3	4	5	6	7	8	9	10
YD085-01	1.12T	1.12	2.24	1.12	2.24	1.6	1.12	1.12	2.3	1.68	1.12
YD085-02	2T	2	4	2	4	2.8	2	2	4.2	3	2
YD085-03	3.15T	3.15	6.3	3.15	6.3	4.4	3.15	3.15	6.6	4.7	3.15
YD085-05	5.3T	5.3	10.6	5.3	10.6	7.4	5.3	5.3	11.2	7.8	5.3
YD085-08	8T	8	16	8	16	11.2	8	8	16.8	12	8
YD085-10	10T	10	20	10	20	14	10	10	21	15	10
YD085-15	15T	15	30	15	30	21	15	15	31.5	22.5	15
YD085-20	20T	20	40	20	40	28	20	20	42	30	20